

# Technical data sheet for GAS COOKTOPS 300mm

G512D-B, G512C-B

- Heavy-duty construction
- 28 MJ/hr open burners
- Flame failure standard
- Pilot burners optional
- 300mm griddle plate option
- Optional simmer plates
- Stainless steel exterior
- Easy clean
- Easy service
- Fully modular



**Overall Construction** 

#### Cooktop

- Welded hob with 1.5mm 304 stainless steel bull nose
- Side panels 1.2mm 304 stainless steel
- Splashback 1.2mm 304 stainless steel
- Vitreous enamelled control panel
- Aluminised steel internal construction
- Cast iron 28MJ/hr open burners with forged brass cap
- Vitreous enamelled cast iron potstands
- Vitreous enamelled open burner spill cover
- Cast iron simmer plates (optional extra)
- 12mm thick mild steel griddle plate
- 2.5mm 304 stainless steel griddle splash guards
- Stainless steel spill trays

#### Bench mount (supplied as –B model)

- Four 63mm dia. heavy-duty 1.2mm 304 stainless steel bench legs with adjustable feet
- Adjustable height 80mm 105mm

#### Controls

- Variable high to low controls to open burners
- Open burners flame failure standard with pilot burners optional
- Variable high to low controls to griddles
- Griddles standard with pilot, flame failure and piezo ignition
- Large easy use control knob heat resistant reinforced
- Easy view control settings on knob

# **Cleaning and Servicing**

- $\bullet$  All models with easy clean stainless steel external finish
- Lift off burner heads and vitreous enamelled burner spill covers
- Stainless steel spill trays under open burner and
- griddle section • Access to all parts from front of unit

# Technical data sheet for GAS COOKTOPS 300mm

#### Specifications

Burners Open Burners 28MJ/hr dual flame ring with simmer rate Griddle Burners 20MJ/hr

 Gas power

 G512D
 56 MJ/hr, 15.5kW

 G512C
 20 MJ/hr, 5.5kW

Griddle Plate 300mm Griddle cooking surface 292mm x 475mm, 1387cm2

Gas connection R <sup>1</sup>/2 (BSP) male All units supplied with Natural and LP gas regulator

### Dimensions

Width 300mm Depth 812mm Height 315mm Incl. splashback 485mm

#### Packing data


0.20m3 Width 870mm Depth 350mm Height 665mm

#### Gas types

Available in Natural gas and LP gas, please specify when ordering Units supplied complete with gas type conversion kits Other gas types on request

#### Options

Simmer plates (replaces Potstand) Ribbed griddle





G512D-B

100

## MOFFAT

Australia www.moffat.com.au New Zealand www.moffat.co.nz

www.bluesealevolution.com

Australia Moffat Pty Limited

## Victoria/Tasmania

740 Springvale Road Mulgrave, Victoria 3170 Telephone 03-9518 3888 Facsimile 03-9518 3833 vsales@moffat.com.au

#### New South Wales

Telephone 02-8833 4111 nswsales@moffat.com.au

South Australia Telephone 03-9518 3888 vsales@moffat.com.au

Queensland Telephone 07-3630 8600 qldsales@moffat.com.au

Western Australia Telephone 08-9202 6802 bgarcia@moffat.com.au

#### New Zealand Moffat Limited

Christchurch 16 Osborne Street Christchurch 8011 Telephone 03-389 1007 Facsimile 03-389 1276 sales@moffat.co.nz

Auckland Telephone 09-574 3150 sales@moffat.co.nz



ISO9001 Quality Management Standard

d and manufactured h

# MOFFAT

ISO9001 All Blue Seal products are designed and manufactured by Moffat using the internationally recognised ISO9001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.



In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

Printed in China © Copyright Moffat Ltd Moffat/4825/BH/2.5M/12.06



